


1. TYPE OF FENCING TO BE USED SHALL COMPLY WITH MNDOT 3886.1 UNLESS INDICATED OTHERWISE ON PLANS
2. DIG A 6"x6" TRENCH ALONG THE INTENDED FENCE LINE.
3. DRIVE ALL POSTS INTO THE GROUND AT THE DOWNHILL SIDE OF THE TRENCH.
4. WIRE FENCING PER MNDOT SPEC. 3886. WIRE MESH MUST BE A MINIMUM OF 2" INTO THE GROUND AND NO MORE THAN 36" ABOVE THE ORIGINAL GROUND SURFACE.
5. FILTER FABRIC PER MNDOT SPEC. 3886. FABRIC APPARENT OPENING SIZE (AOS) SHALL BE 30 TO 80 IN AREAS OF COARSE GRAINED SOILS, AND 50 TO 80 IN AREAS OF FINE GRAINED SOILS.
6. LAY OUT SILT FENCE ON THE UPHILL SIDE ALONG THE FENCE LINE, AND BACK FILL.
7. WOOD POSTS MAY BE SPACED UP TO 4 FEET APART IF WIRE MESH IS NOT USED TO SUPPORT THE FABRIC. IF WIRE MESH IS USED TO SUPPORT THE FABRIC STEEL POSTS MAY BE SPACED UP TO 8 FEET APART.



CITY OF ZIMMERMAN



A Tyco International Ltd. Company

SILTE FENCE DETAIL

PLATE NO.
GC-2

DATE:
FEB. 2005